










TUFFGRIP PS-99

FIRM-SET MODIFIED TRANSITIONAL PSA

RH	pH	MVER	FLASH TIME	WORKING TIME	CURE TIME	LIGHT TRAFFIC	HEAVY TRAFFIC	ROLLING LOADS
								
99%	5-12	12 lbs	30-60 MIN*	12 HRS	12 HRS	0 MIN*	24 HRS	48 HRS

APPROVED FLOORING TYPES

- **RESILIENT:** Linoleum, Modular (LVP, LVT, rigid core [dryback], SVT, VET, VCT), Rubber (crumb, sheet, tile), Sheet (fiberglass, heterogeneous, homogeneous), Stair Treads (rubber, vinyl)
- **CARPET:** Broadloom (6-ft vinyl-backed, Action-Bac, jute-back, double-stick -carpet-to-cushion & cushion-to-substrate, hot-melt-backed, HP- & vinyl-backed, non-vinyl-backed patterned, polyurethane, rubber-backed, unitary & unitary Action-Bac, woven-backed) Modular (hard-backed, soft-backed, walk-off)
- **WOOD:** Cork (cork-backed hard surface, underlayment)

WHY USE

- Aggressive tack, fast grab
- High moisture tolerance
- High-strength, water-resistant bond
- Repositionable installation
- Immediate access for light traffic
- Handles heavy rolling loads
- Attractive price point
- Installs multiple flooring types
- 12 hours of working time
- Simple installation
- Elastomeric bond
- Plasticizer migration resistance
- Low VOC, extremely low odor
- Antimicrobial technology

CERTIFICATIONS



COVERAGE: 90-350 ft²/gal
AVAILABLE IN: 1 and 4 gal
SHELF LIFE: 2 years